

Feel pure, clean, and fresh air as you are amid the nature by Mitsubishi Electric Wall-mounted ventilator for your health and be comfortable everywhere.



EX-20SH5T (8 inches) EX-25SH5T (10 inches) EX-30SH5T (12 inches)




FOR SHOPS, OFFICE ROOMS, LIVING ROOMS & KITCHENS

- Operates quietly Easy to clean
- Energy efficient

## **Wall Mounted Type** wooden frame inner dimensions

EX-20SH5T... 250 EX-25SH5T... 300 EX-30SH5T... 350





Wooden frame are not supplied

DIN	MEN	ISIO	NS

Unit : r												
MODEL	A	В	С	D	E	F	G	н	J			
EX-20SH <sub>5</sub> T	296	120	265	320	36	40	240	50	250			
EX-25SH <sub>5</sub> T	346	170	315	370	32	57	290		300			
EX-30SH <sub>5</sub> T	396	220	365	420	45	70	340	-	350			

MODEL Rated Voltage Frequency Ex	Rated Voltage	Rated Voltage Frequency		Rated Current	Power Consumption	RPM	Airflow Rate		Noise Level	Weight
	Exhaust/Supply (A)	(W)	NFW.	m³/h	CFM	(dB)	(kg)			
EX-20SH <sub>5</sub> T			-	0.10	19.	1330	580	341	39	2.2
EX-25SH <sub>5</sub> T	220	50	Exhaust	0.12	25	1160	930	547	39	2.5
EX-30SH <sub>5</sub> T				0.15	31	900	1160	683	37	2.9



EX-20SHC5T (8 inches) EX-25SHC5T (10 inches) EX-30SHC5T (12 inches)

## FOR SHOPS, OFFICE ROOMS, LIVING ROOMS & KITCHENS

- Operates quietly Easy to clean
- Energy efficient

EX-20SHC5T EX-25SHC5T

Specially designed with an Oil-Catcher

## **Wall Mounted Type**

wooden frame inner dim EX-20SHC5T... 250

EX-25SHC5T... 300 EX-30SHC5T... 350

ns	_ A _			EX-30SF
	В	,	H 90 F	90
		4 1	E	E
		U		-
		٥		
	Autylesa	8	4 4	1 4
	201985	18	U	
•				

90 F	
	Wooden frame
	Nooden frame are

MODEL	

DIMENSIONS												
MODEL	A	В	С	D	E	F	G	н	J			
EX-20SHC <sub>5</sub> T	296	120	265	320	36	40	240	50	250			
EX-25SHC5T	346	170	315	362	50	57	290	15	300			
EX-30SHC5T	396	220	365	412	65	70	340	-	350			

MODEL	Rated Voltage	Frequency	Exhaust/Supply	Rated Current	Power Consumption	RPM	Airflox	v Rate	Noise Level	Weight
	(V)	(Hz)	Exhaust Supply	(A)	(W)	nrW	m³/h	CFM	(dB)	(kg)
X-20SHC7	220	\$65.00		0.10	19	1330	580	341	39	2.2
EX-20SHC <sub>5T</sub>	230 5	50	Exhaust	0.08	17	1300	550	324	37	
LX-20011091	240			0.08	19	1330	560	330	37	
	220	60		0.11	24.5	1565	670	394	42	
X-25SHC7	220	\$72.00		0.12	25	1160	930	547	39	2.7
	230	50	F. b	0.11	25	1130	930	547	38	
EX-25SHC <sub>5T</sub>	240		Exhaust	0.11	26	1160	940	553	39	
	220	60		0.15	33	1190	970	571	40.5	
EX-30SHC7T	220	\$109.00		0.15	31	900	1160	683	37	
	230	50	E.ht	0.14	31	860	1180	695	36	3.2
EX-300HOSI	240		Exhaust	0.14	33	930	1240	730	38	3.2
	220	60		0.19	41	880	1100	647	36	